AMENDMENTS TO THE CLAIMS

1. (Previously presented) A dental implant system, comprising:

a dental implant including a body portion and an abutment portion that is integrally formed with the body portion, the implant body portion located at a distal end and configured to lie at least partially below a crest of a patient's jawbone, the abutment portion located at a proximate end of the implant and configured to lie at least partially above the crest of the patient's jawbone, the abutment portion comprising a flared portion, a shoulder portion and a final restoration portion, the shoulder portion lying between the flared portion and the final restoration portion, the dental implant further including a bore that extends generally along the longitudinal axis of the dental implant from a top surface of the abutment portion, the bore including an notch configured to releasably receive one or more lever arms or prongs on a mating component; and

a mating component including one or more lever arms or prongs configured to engage the notch.

- (Canceled)
- 3. (Original) The dental implant system of Claim 1, wherein the body portion and the abuttment portion of the implant are machined from a single piece of material.
- 4. (Currently amended) The dental implant system of Claim 1, wherein the [[cap]] mating component further includes a tissue retention flange at the distal end that extends below the shoulder portion when the healing cap mating component is coupled to the abutment portion.
- (Previously presented) The dental implant system of Claim 4, wherein the tissue retraction flange also extends away from the flared portion forming a gap between the tissue retraction flange and the flared portion.
- (Currently amended) The dental implant system of Claim 1, wherein the body
 portion of the [[cap]] mating component includes a base portion that is configured to rest at least
 partially on the shoulder portion of the abutment portion.
- (Previously presented) The dental implant system of Claim 1, wherein the body portion of the dental implant includes a bone apposition surface.
- (Currently amended) The dental implant system of Claim 1, wherein the [[cap]] mating component is white.

- (Currently amended) The dental implant system of Claim 1, wherein the [[cap]]
 mating component has a color that is substantially the same a natural tooth.
- (Currently amended) The dental implant system of Claim 1, wherein the abutment portion and the [[cap]] mating component have round cross-sections.
- 11. (Currently amended) The dental implant system of Claim 1, wherein the abutment portion and the [[cap]] mating component have non-round cross-sections.

12-17. (Canceled)

- 18. (Original) The dental implant system of Claim 1, in combination with a coping for creating a final restoration, the coping comprising a body portion having a proximal end, a distal end and an inner surface that defines an internal cavity and at least one standoff that extends from the inner surface towards a center of the internal cavity.
- (Original) The dental implant system of Claim 18, wherein the at least one standoff extends at least about 25 microns from the inner surface.
- (Original) The dental implant system of Claim 19, wherein the at least one standoff extends less than about 50 microns from the inner surface.
- 21. (Original) The dental implant system of Claim 18, wherein the coping is made of a material that can be melted and removed from a mold during an investment casting process.
- (Original) The dental implant system of Claim 21, wherein the coping is made of plastic.
- 23. (Original) The dental implant system of Claim 22, wherein the coping is made from a material that is suitable for forming a portion of the final restoration.
- (Original) The dental implant system of Claim 23, wherein the coping is made of gold.
- (Original) The dental implant system of Claim 23, wherein the coping is made of a ceramic material.
- (Original) The dental implant system of Claim 18, wherein the at least one standoff has a tapered shape.
- (Original) The dental implant system of Claim 18, further comprising a flanged region that configured to rest upon a shoulder of a final abutment.
- (Currently amended) A method for installing a prosthetic tooth, comprising the steps of:

inserting a distal end of a body portion of a single stage dental implant having a body portion, an abutment portion and an internal bore having a notch into a patient's iawbone:

engaging a lever arm or prong of a matting mating component to the notch in the internal bore to releaseably couple [[a]] the mating component to the dental implant;

coupling a healing cap to the abutment portion such that the abutment portion is positioned within an internal cavity of the healing cap; and

removing the healing cap from the abutment portion.

- 29. (Previously presented) A method as in Claim 28, wherein the step of coupling a healing cap to an abutment portion, further includes using a healing cap screw to couple the healing cap to the abutment portion.
 - 30. (Original) A method as in Claim 28, further comprising providing an impression cap with an injection port and a plurality of vent holes; positioning the impression cap onto the abutment portion of the implant; and injecting a first impression material into the impression cap through the injection port until the first impression material is extruded through at least one of the vent holes.
- 31. (Original) A method as in Claim 30, wherein the step of positioning the impression cap onto the abutment portion includes snapping the impression cap onto the shoulder of the abutment portion.
- 32. (Original) A method as in Claim 30, further including the steps of taking an impression of the patient's mouth by placing an impression tray filed with a second impression material over the impression cap and removing the impression tray and the impression cap from the patient's mouth.
- (Original) A method as in Claim 30, further including modifying the shape of the abutment portion.
- 34. (Original) A method as in Claim 30, wherein the step of injecting the first impression material into the impression cap includes inserting a tip of a syringe filled with the first impression material into the injection port of the impression cap.
 - 35. (Original) A method as in Claim 28, further comprising:

providing a coping having a body portion that comprises a proximal end, a distal end and an inner surface that defines an internal cavity and at least one standoff that extends from the inner surface towards a center of the internal cavity;

providing an analogue of the abutment portion of the dental implant,

placing the coping over the analogue;

applying a material suitable for investment casting to an outer surface of the coping;

encasing the coping and the material suitable for investment casting in an investment material:

melting the coping and the material suitable for investment casting;

removing the coping and the material suitable for investment casting from the investment material; and

filling a cavity within the investment material with a material suitable for forming a part of a final restoration.